

AM




PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification <sup>6</sup> : <b>G11B 33/04</b></p>	<p><b>A1</b></p>	<p>(11) International Publication Number: <b>WO 98/57328</b> (43) International Publication Date: 17 December 1998 (17.12.98)</p>
<p>(21) International Application Number: PCT/US98/12431 (22) International Filing Date: 12 June 1998 (12.06.98) (30) Priority Data: 08/874,772 13 June 1997 (13.06.97) US (71) Applicant: IOMEGA CORPORATION [US/US]; 1821 West Iomega Way, Roy, UT 84067 (US). (72) Inventors: WILLIAMS, Kristi; 966 East Kiely Boulevard, Santa Clara, CA 95051 (US). SALISBURY, Shaun; 2485 Shorline Drive, Alameda, CA 94501 (US). (74) Agents: KURTZ, Richard, E. et al.; Woodcock Washburn Kurtz Mackiewicz &amp; Norris LLP, 46th floor, One Liberty Place, Philadelphia, PA 19103 (US).</p>		<p>(81) Designated States: CA, JP, SG, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>

(54) Title: CASE FOR PACKAGING AND STORING A MAGNETIC DISK CARTRIDGE



(57) Abstract

A case for packaging and storing a magnetic disk cartridge is disclosed. The case includes a tray that slides into a housing, and a seal between the tray and the housing. The seal protects the cartridge from dust and contaminant infiltration and from physical damage. The tray forms a receptacle for receiving and holding the cartridge and includes a hinge for enabling a front portion of the tray to pivot downward to provide clearance to insert and remove the cartridge by sliding therein. The case includes a latching means for latching the tray and housing together, a transparent panel for viewing the cartridge while it is inside the case, a clasp that prevents the tray from being fully removed from the housing, and unique key members that mate to corresponding key grooves in a JAZ cartridge.

BEST AVAILABLE COPY

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

**CASE FOR PACKAGING AND STORING A  
MAGNETIC DISK CARTRIDGE**

**Field of the Invention**

This invention relates to handling small items,  
5 and more particularly, relates to packaging and storing a  
magnetic disk cartridge.

**Background of the Invention**

Disk cartridges for information storage typically  
comprise one or more disks that are housed in a hard plastic  
10 shell. The disks have a hub located near the disk center,  
and the shell has an aperture that provides access for a  
disk drive spindle motor to engage the disk hub. The  
cartridge typically also has a head opening for enabling a  
read/write head to access information stored on the disk.  
15 The head opening is typically covered by a moveable closure,  
such as, for example, a spring load shutter or a sliding  
flexible door member.

Advances in disk and disk drive technology have  
provided disk cartridges with increasing speed and data  
20 storage capacity. Along with increased speed and capacity,  
such cartridges often have greater probability for dust and  
gaseous chemical contamination of the disk media, and have  
high cost. Moreover, the information that is stored on such  
cartridges often has value worth many times the price of the  
25 cartridge. Future advances will likely increase the  
cartridge value.

- 2 -

Figure 7 (Prior Art) shows a JAZ cartridge 100, which illustrates such advantages and features. The JAZ cartridge, which is produced by the assignee of the present invention, is described in U.S. Patent Des. 378,518 (Summer et al.) and is incorporated herein by reference in its entirety. Cartridge 100 has a substantially perpendicular box shape, except for its access end (that is, the end having the flexible door) that has a partly rectilinear and partly arcuate shape. Cartridge 100 houses a disk (not shown) for storing magnetic information.

Dust infiltration into a cartridge may interrupt or corrupt the information stored on the disk. Physical damage may break the shell or cause the stored information to become unrecoverable. Such damage may occur during shipping, handling, or storage of the cartridge.

It is therefore desirable to provide a device that protects a disk cartridge from physical damage and from dust infiltration, and that is easy to use.

#### Summary of the Invention

A case for holding a magnetic disk cartridge is provided. The case may be employed for packaging the cartridge before the cartridge is sold to an end user. Alternatively, the case may be supplied separately from the cartridge. Regardless of the means by which a user acquires it, the case protects the cartridge from physical damage and augments protection against dust and gaseous chemical infiltration while the cartridge is disposed therein.

The case according to the present invention comprises a housing, a tray, and a seal. The tray has a bottom planar member, a front panel, two side walls, a curved rear wall, and front tabs and rear tabs that extend from the side walls. The side walls, tabs, and bottom member form a receptacle, into which a disk cartridge may slide. Rectangular key members protrude from the top and bottom corners of one side of the tray into the receptacle. The top key member has different dimensions from the bottom

- 3 -

key member, each of which mate to corresponding square notches on the corners of the disk cartridge, which are described in U.S. Patent Application Serial No. 08752823, filed November 20, 1996, which is incorporated herein by  
5 reference in its entirety. The key members assure proper orientation of the cartridge during insertion into the tray, and enhance the tightness of fit between the tray and the cartridge.

The tray also has a hinge that separates a tray  
10 front portion from a tray rear portion. The tray is capable of sliding into and out of an opening in a front of the housing. If the tray is translated out of the housing opening far enough to expose the hinge, the tray front portion may be pivoted downward, which enables the disk  
15 cartridge to slide into or out of the receptacle.

The seal is located on a front portion of the tray just inside of the tray front panel. The front panel and the seal substantially obstruct the housing opening while the tray is in the fully inserted position. Because the  
20 disk cartridge is fully enclosed by the case while the tray is fully inserted in the housing, the case protects the disk cartridge from physical damage as well as from dust and chemical contaminant infiltration.

The case also includes latching means for holding  
25 the tray within the housing while in the fully inserted position, a gripping surface that is used to unlock the latching means, and a clasp that limits the outward travel of the tray relative to the housing.

#### Brief Description of the Drawings

30 Figure 1 is a perspective, exploded view of the case according to the present invention showing the tray, seal, and housing;

Figure 2 is a perspective view of the housing with the tray in the fully inserted position;

35 Figure 3 is a perspective view of the tray removed from the housing and seal;

- 4 -

Figure 4 is a sectional view of a portion of the tray of Figure 3;

Figure 5 is a perspective view of the housing;

Figure 6 is a perspective view of the seal; and

5        Figure 7 is a view of a conventional cartridge of the type that may be employed by the case of Figure 1.

#### Description of the Preferred Embodiment

Referring generally to the Figures, wherein the reference numerals are used consistently throughout the  
10 views, there is shown a case for packaging and storing a magnetic disk cartridge according to the preferred embodiment of the present invention. Although a case 10 according to the present invention is described having a shape that corresponds to a conventional cartridge 100, the  
15 present invention is not limited thereto. The present invention, rather, encompasses a case 10 that is formed to receive any magnetic disk cartridge, including a conventional JAZ cartridge shape, a cartridge that is of similar shape and size to the conventional JAZ cartridge  
20 shape, and a cartridge that is of dissimilar shape and size to the conventional JAZ cartridge shape.

Referring specifically to Figures 1 and 2, a case 10 comprises a housing 12, a tray 14 that is insertable into housing 12, and a seal 13. Referring to Figures 1, 2, and  
25 5, housing 12 comprises a planar top member 16, a planar bottom member 18, a rear member 20, two opposing side members 22, and an opening 24. Top member 16 and bottom member 18 form substantially parallel planes. Side members 22 form substantially parallel planes that each join to top  
30 member 16 and bottom member 18. Rear member 20 is preferably rectilinear and is attached to each side, top, and bottom members 22, 16, and 18, respectively, to form a box-like shape. On the end opposing rear member 20, housing 12 forms an opening 24. The end having opening 24 will  
35 hereinafter be referred to as a cartridge "front" end. Specifically, a front edge of each top member 16, bottom

- 5 -

member 18, and side members 22 form opening 24. Because opening 24 receives tray 14 therethrough, opening 24 is preferably substantially rectangular. Top member 16 has a semi-circular cut-out portion 17 that provides access to a grip 46, as will be described more fully below. Cut out portion 17 is proximate opening 24.

Referring to Figures 1, 2, and 3, tray 14 comprises a bottom planar member 26, a front panel 28, two opposing side walls 30, a rear wall 32, two rear tabs 48, and two front tabs 50. Bottom member 26 is joined to each side wall 30, front panel 28, and rear wall 32. Front panel 28 has a raised lip 25 and a semi-circular serrated grip 46 disposed on top of front panel 28 proximate lip 25. Each side wall 30 is substantially perpendicular to front panel 28, and joined thereto. Rear wall 32 forms an oblique angle where joined to each side wall 30. Rear wall 32 has two rectilinear surfaces, 42a and 42b, which each have one end that is connected to a side wall 30. Rectilinear surfaces 42a and 42b are connected therebetween by an actuate surface 44. Rear tabs 48 are disposed adjacent side walls 30 and rear wall 32. Front tabs 50 are disposed on opposing side walls 30. Each tab 48 and 50 extend from housing walls toward an interior of tray 14.

Bottom planar member 26 has two raised sliding surfaces 66 for slidably receiving cartridge 100. Each of the sliding surfaces 66 has a cantilevered clasp 68 that rides in a groove 70, which is partially shown in Figure 5, that is disposed on an interior surface of housing bottom member 18. Preferably, housing 14 has two clasps (not shown) disposed on an interior bottom surface of the housing that ride in grooves disposed on the underside (not shown) of sliding surfaces 66.

Front panel 28 has a front panel interior surface 29, each side wall 30 has a side wall interior surface 31, and member 26 has a bottom interior surface 27. Interior wall surfaces 29, 31, 42a,b, and 44, and sliding surfaces 66 form the perimeter boundaries of a receptacle 34 for

- 6 -

receiving a magnetic disk cartridge 100 of the type shown in Figure 7. Bottom member surface 27 and tabs 48 and 50 form the upper and lower boundaries, respectively, of receptacle 34. Preferably, receptacle 34 has dimensions that are  
5 slightly larger than the particular magnetic disk cartridge that is received. Receptacle 34 preferably has a width of approximately 3.90625 inches, a height of approximately 0.46875 inches, and an overall length of 4.03125 inches. The overall receptacle length comprises a rectilinear  
10 portion of approximately 3.34375 inches, and a curved portion of approximately 0.6875 inches. These receptacle dimensions correspond to dimensions of cartridge 100 plus 0.03125 inches added for clearance.

Referring to Figure 4, which is a sectional view  
15 taken through one side of tray 14, the tray includes a top key member 60 and a bottom key member 62 disposed on one of the side walls 30. Preferably, key members 60, 62 are disposed on corners of the tray so as to protrude into receptacle 34. Top key member 60 is significantly taller  
20 than bottom key member 62 so as to mate to corresponding key grooves 102 and 104 on cartridge 100. Top key groove 102 and bottom key groove 104 are shown in Figure 7.

Each wall 34 has a hinge 36, that is formed therein by slot 38. The portion of wall 30 below slot 38  
25 forms a flex portion 40 that enables a front portion 52 to pivot from a rear portion 54. Preferably, front tabs 50 are located on rear portion 54 near slot 38. When cartridge 100 is positioned within receptacle 34, the plane formed by disk 58 is substantially parallel to a plane formed by bottom  
30 member surface 27.

Referring to Figures 1, 2, and 6, seal 13 is preferably located on a front portion of tray 14 immediately to the rear of lip 25. Because seal 13 cooperates with tray 14 and opening 24, seal 13 has approximately the same  
35 profile as opening 24. A semi-circular, serrated grip 46 is preferably attached to the rear, top portion of seal 13. Grip 46 mates with cut-out portion 17 while tray 14 is fully



- 7 -

inserted into housing 12. Preferably, seal 13 and grip 46 are formed as a single integral piece, as shown in Figure 6.

The case 10 includes a latching means that includes a latch member 56 disposed on the front portion of tray 14 immediately to the rear of grip 46. Housing 12 has a cavity 58 (shown in relief in Figure 5) that aligns with latch member 56 when tray 14 is in the fully inserted position.

Preferably, housing 12 is formed from an engineering plastic, for example polystyrene or polypropylene, of sufficient strength to withstand forces commonly encountered by such devices and of sufficient impact resistance to withstand common impacts, such as dropping. Tray 14 is preferably formed from an engineering plastic, for example polystyrene or polypropylene, of sufficient flexibility to permit flex portion 40 and hinge 36 to function as described herein. Seal 13 may be formed of flexible or compressible material, for example rubber, so as to enhance contact between housing 12, seal 13, and tray 14.

Case 10 is preferably employed as retail packaging for a cartridge such that the cartridge may be sold contained in case 10. To operate such a case 10, a user preferably grasps in one hand tray 14 by grip 46 and by lip 25 between a first thumb and forefinger, while simultaneously holding housing 12 in another hand. By squeezing together the first thumb and forefinger, the user depresses the part of the tray that has latch member 56 located thereon. The tray deflects until latch member 56 comes out of cavity 58, thereby enabling tray 14 to be pulled from housing 12. By pulling housing 12 and tray 14 apart, the user may urge tray 14 from housing 12. Tray 14 is translated outward from housing opening 24 until hinge 36 is substantially even with the front edge of opening 24. A short distance after hinge 36 emerges from opening 24, clasp 68 contacts the end of groove 70, thereby preventing further outward travel of tray 14 relative to housing 12. Because

- 8 -

hinge 36 is outside of housing 12, the user may pivot tray front portion 52 downward from rear portion 54 via hinge 36, thereby enabling cartridge 100 to clear front panel 28.

Cartridge 100 is thus capable of sliding out of tray 14 by manual pulling. Because bottom member surface 27 and tabs 48 and 50 prevent cartridge 100 from pivoting, cartridge 100 is removed from tray 14 by grasping cartridge 100 and pulling thereapart. Tabs 48 and 50 may be formed of flexible material so as to ease removal of cartridge 100 from receptacle 34.

To load cartridge 100 into case 10, tray 14 may be translated outward from housing 12 and pivoted downward as described above. Cartridge 100 may then slide over front panel 28, over bottom member surface 27, beneath front tabs 50 and eventually beneath rear tabs 48. After cartridge 100 clears front panel 28, tray front portion 52 may be pivoted upward until tray 14 is positioned for sliding into housing 12. Sliding members 66, tabs 48 and 50, and corners of the tray are preferably oriented so that only the corners and edges of cartridge 100 are in contact with tray 14.

When tray 14 is fully inserted into housing 12, lip 25 and seal 13 is proximate opening 24. Preferably, lip 25 and seal 13 contact the front edge of top member 16, bottom member 18, and each side member 22, thereby inhibiting dust and chemical contaminants from infiltrating into the case 10 when tray 14 is full inserted therein. A tight fit between seal 13 and housing 12, between grip 46 and cut out 17, and between seal 13 and lip 25 enhance such inhibition to infiltration, especially because wall 28 must be wide enough to support grip 46.

Although certain embodiments of the present invention have been disclosed and described with particularity, these embodiments are provided for the purpose of illustrating the invention and are not meant to be limiting. Upon review of the foregoing specification, those of skill in the art will immediately realize that numerous variations, modifications and adaptations of the

- 9 -

invention are possible. Although differing in form and function, such alternate embodiments will employ the spirit of the present invention and are encompassed by the same. Accordingly, reference should be made to the appended claims  
5 in order to determine the full scope of the present invention.

- 10 -

What is claimed is:

1. A case for holding a magnetic disk cartridge having a disk that defines a disk plane, comprising:
  - a housing having an opening; and
  - 5 a tray including a substantially planar bottom member and a receptacle capable of receiving a magnetic disk cartridge, said bottom member defining a coincident tray bottom plane, said receptacle capable of receiving the disk cartridge having a disk plane that is
  - 10 substantially parallel to said tray bottom plane while the cartridge is disposed within the receptacle, said tray being slidably insertable into said opening and being slidably extractable therefrom, said tray being capable of substantially obstructing the opening while said tray is in
  - 15 a fully inserted position.
2. The case of claim 1 wherein said tray includes a hinge disposed therein, said hinge enabling a front portion of said tray to pivot relative to a rear portion of said tray.
- 20 3. The case of claim 1 further comprising a seal disposed on the tray proximate the opening while the tray is in the fully inserted position.
4. The case of claim 1 wherein the tray has a front panel coupled to the bottom member, said front panel
- 25 capable of substantially obstructing the housing opening while the tray is in the fully inserted position.
5. The case of claim 4 further comprising a seal that is disposed between the front panel of the tray and a front edge of the housing while the tray is in the fully
- 30 inserted position, the seal capable of inhibiting contaminants from passing therethrough.
6. The case of claim 4 wherein the tray further

- 11 -

includes two side walls and a rear wall, each one of said two side walls and said rear wall being coupled to said tray bottom member, each one of said two side walls having an end coupled to said front face and an other end coupled to said rear wall, said bottom member forming a bottom surface, each one of said two side walls forming a side surface, said rear wall forming a rear surface; said bottom surface, said two side surfaces, and said rear surface defining at least a part of the receptacle.

10                   7.    The case of claim 6 wherein the rear wall comprises an arcuate surface.

                  8.    The case of claim 6 wherein said rear wall forms a first rectilinear surface that obliquely extends from a back end of one of the rear surfaces, a second  
15 rectilinear surface that obliquely extends from a back end of an other one of the rear surfaces, and an arcuate surface coupled between said first rectilinear surface and said second rectilinear surface.

                  9.    The case of claim 1 wherein said tray  
20 includes a gripping surface disposed thereon capable of facilitating gripping of said tray during insertion and extraction of said tray from said housing.

                  10.   The case of claim 1 wherein said receptacle receives a cartridge having a width that is approximately  
25 3.875 inches, a height that is approximately 0.4375 inches, and an overall length of approximately 4.0 inches, said overall length comprising a first rectilinear portion that is approximately 3.3125 inches.

                  11.   The case of claim 8 wherein said receptacle  
30 has a width that is approximately 3.90625 inches, a height that is approximately 0.46875 inches, and an overall length of approximately 4.03125 inches, said overall length

- 12 -

comprising a first rectilinear portion that is approximately 3.34375 inches; whereby said receptacle has a shape that substantially corresponds to the cartridge shape plus a clearance.

5           12. The case of claim 1 wherein the tray includes multiple tabs disposed proximate an upper portion of the tray, the multiple tabs defining an upper boundary of at least part of the receptacle.

10           13. The case of claim 2 wherein said tray includes:

two rear tabs disposed on an upper portion of the tray, one of said two rear tabs coupled to a rear wall and a side wall, an other of said two rear tabs coupled to the rear wall and an other side wall; and

15           two front tabs disposed proximate an upper portion of the tray, one of said two front tabs coupled to one of the side walls, an other of said two front tabs coupled to an other one of the side walls, said front tabs disposed on the tray rear portion proximate the hinge.

20           14. The case of claim 13 wherein the bottom member, the rear tabs, and the front tabs form at least part of the receptacle therebetween.

25           15. The case of claim 1 further comprising a means for latching the tray to the housing while the tray is in the fully inserted position.

30           16. The case of claim 1 further comprising a first key member disposed on the tray and protruding therefrom into the receptacle, the first key member being capable of slidable insertion into a corresponding key groove disposed on the disk cartridge.

17. The case of claim 16 further comprising a

- 13 -

second key member disposed on the tray and protruding therefrom into the receptacle, the second key member having a cross sectional profile that is substantially different from a cross sectional profile of the first key member and  
5 being capable of slidable insertion into a corresponding key groove disposed on the disk cartridge.

18. The case of claim 1 wherein the housing includes a top planar member having a substantially transparent panel disposed therein that is capable of  
10 enabling at least a portion of the disk cartridge to be seen from the exterior of the case while the cartridge is disposed within the case and the tray is in the fully inserted position.

19. A case for holding a disc cartridge  
15 comprising:

a shell forming a receptacle therein for slidably receiving the disc cartridge;

a first key member and a second key member that are disposed on the shell and project therefrom into  
20 the receptacle, the first key member capable of slidable insertion into a corresponding key groove disposed on the cartridge, the second key member capable of slidable insertion into a corresponding key groove disposed on the cartridge, the first key groove having a cross sectional  
25 profile substantially different from a cross sectional profile of the second key member.

1/6




FIG. 1



2/6





FIG. 2



4/6




FIG. 5

5/6





FIG. 6

6/6

FIG. 7  
Prior Art



# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/US 98/12431

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 G11B33/04

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G11B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 502 572 A (PHILIPS NV) 9 September 1992	1, 19
A	see column 2, line 21 - line 29 see column 3, line 54 - column 5, line 25; figure 9	2-18
Y	EP 0 632 454 A (SONY CORP) 4 January 1995 see column 10, line 30 - column 13, line 24	1, 19
Y	US 4 627 531 A (CLEMENS PHILIP M) 9 December 1986 see column 3, line 28 - column 4, line 52	1, 19
A	US 5 531 324 A (KOSAKI SHINICHI ET AL) 2 July 1996 see column 2, line 52 - column 3, line 53	1-19



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

### \* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

25 September 1998

Date of mailing of the international search report

05/10/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Ressenaar, J-P

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 98/12431

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0502572 A	09-09-1992	NL 9100386 A JP 4327168 A US 5219090 A	01-10-1992 16-11-1992 15-06-1993
EP 0632454 A	04-01-1995	CN 1101745 A JP 7052988 A	19-04-1995 28-02-1995
US 4627531 A	09-12-1986	US 4627532 A	09-12-1986
US 5531324 A	02-07-1996	JP 7187274 A JP 8018631 B	25-07-1995 28-02-1996

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**